



EXTENDED LIFE **GOLD** ANTIFREEZE/COOLANT



EXTENDED LIFE **GOLD**

ANTIFREEZE/COOLANT AVAILABLE IN
CONCENTRATE OR **50/50 PRE-DILUTED**

IF YOU'RE A CHRYSLER, DODGE, JEEP, FORD, LINCOLN OR MERCURY OWNER, YOU'VE FOUND YOUR MATCH WITH OEM EXTENDED LIFE GOLD.

Meeting or exceeding these particular vehicle specifications, OEM Extended Life GOLD Antifreeze/Coolant provides excellent high temperature aluminum protection and extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals. *When added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, OEM GOLD provides superior performance for these automotive or light duty vehicles.

APPLICATION	RECOMMENDED CHANGE INTERVAL
North American gasoline and light duty diesel vehicles.	150,000 miles* or 5 years of service protection
VEHICLE MAKES	COMPATIBILITY
Chrysler, Dodge, Jeep, Ford, Lincoln, Mercury	For best results, do not mix with conventional high pH coolants.
FORMULATION	PERFORMANCE FEATURE
Ethylene glycol based. Low silicate, phosphate and amine free	Aluminum Compatible
PRODUCT COLOR	PRODUCT OPTIONS
Gold	Concentrate and 50/50 Pre-diluted
SPECIFICATION/ PERFORMANCE LEVEL	RECOMMENDED FOR USE AND FULLY COMPATIBLE WITH PRODUCT MEETING
ASTM D3306 GM1825M, 1899M Chrysler MS7170, MS9769 SAE J1034, JIS K2234 US Fed A-A-870-A	Ford WSS-M97B51-A1

THE RIGHT **MATCH** FOR YOUR **VEHICLE**



O/E/MTM
ORIGINAL EQUIPMENT MANUFACTURER

EXTENDED LIFE **GOLD**



CONCENTRATE



50/50 PRE-DILUTED

ITEM#	UNIT SIZE	UPC#	SCC#
86-734GOEM	1 U.S. Gallon	0-59934-90443-4	400-59934-90443-2

ITEM#	UNIT SIZE	UPC#	SCC#
86-834GOEMFC	1 U.S. Gallon	0-59934-90707-7	400-59934-90707-4

ANTIFREEZE/DE-IONIZED WATER DILUTION CHART

PROTECTION AGAINST FREEZING (°F)	-34	-61	-83
VOLUME % ANTIFREEZE	50	60	70
VOLUME % DE-IONIZED WATER	50	40	30
**PROTECTION AGAINST BOIL-OVER (°F)	264	269	276

**WITH A 100 KILOPASCALS (15 PSI) RADIATOR CAP IN GOOD CONDITION

Never use 100% coolant in concentrated form. A 50% dilution (i.e. when mixed with an equal volume of high quality soft, de-ionized or distilled water) is generally recommended for the best balance of protection against freezing, corrosion and summer boil over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended.

TYPICAL PRODUCT PROPERTIES

CHARACTERISTIC	PERFORMANCE	TEST METHOD
pH	7.5–8.6	ASTM D1287
Specific gravity ^b	1.065–1.080	ASTM D1122
Freeze point (°C/°F)	-37/-34	ASTM D1177
Foam volume (ml)	150 max.	ASTM D1881
Foam break time (second)	5 max.	ASTM D1881
Reserve Alkalinity (ml)	3.0 max.	ASTM D1121
Chloride (ppm)	25 max.	ASTM D3634
Silicon (ppm)	250 max.	ASTM D6130
Color	Gold	
Glycol Content (wtg.%)	47 min.	
Inhibitors and Water Content (wtg.%)	53 max.	

Values shown are for 50-50 pre-diluted coolant. ^b Measured at 15.6°C/60°F